

## Request For Quote -Soft Chute

Quote Information		Support	Mold	Tie Rods
1. Mold Opening (daylight, max is 24"):		Frame		
2. (A) Width between Tie Rods:			<b>A</b> (	
3. (B) Width between Frame:		\( \)	<b>C</b> A	
4. (C) Clearance Height (chute):		<b>(</b>	B -	
5. (D) Machine Clearance mold to base:				D
6. (E) Base to floor:				
7. (F) Width of base:				
8. (G) Desired extension past base:			30°	
9. (H) Desired discharge height:			Typically	<u> </u>
10. Size of parts:		A H	Machine Base	Ē
Length: Width: Height:				<u> </u>
11. Runner system: O Yes	O No	<b>∢▶</b> ◀	FF	<b>→</b>
12. If yes Runner system, runner size is:			\ \ <del>-</del> widt	OPEN
Length: Width: Height:				
13. Do you require high temp material?				
(for parts over 180°) Yes	O No		HEIGHT	
14. Quantity:			TIE ROI	05
All dimensions must be completed for	a Quote to	o be given.	N N N N N N N N N N N N N N N N N N N	30°
		<u> </u>		
Note: All guideskirts come with mounting	hardware.	Standard color is	CHUTÉ LENGTH TYP.	1
Gray. Yellow can be requested at no extra when ordering.				

Soft Chutes have a material bottom only.



Contact Information							
Company Name							
Contact Person							
Address							
City, State, Zip							
Phone	(	)			ext:		
Fax	(	)	-				
E-mail			-				

Please Fax to (815)337-3020 or E-mail to sewing@macautomation.com